

OUTDOOR FABRICS

TenCate tentdoek kwaliteiten

Bijzondere eigenschappen:

TENCATE Cotton™



Samenstelling	Gewicht	Waterkolom (ISO 811)	Kleurechtheid (ISO 105 B04)	Artikel
100% katoen	210 gr/m ²	≥ 25 cm	≥ 4	KD-22
100% katoen	280 gr/m ²	≥ 30 cm	≥ 4	KD-38
100% katoen	310 gr/m ²	≥ 40 cm	≥ 4	KD-48
100% katoen	340 gr/m ²	≥ 40 cm	≥ 4	KD-24

TENCATE Solair™



Samenstelling	Gewicht	Waterkolom (ISO 811)	Kleurechtheid (ISO 105 B04)	Artikel
50% polyester / 50% katoen	250 gr/m ²	≥ 30 cm	≥ 4	KA-10
50% polyester / 50% katoen	330 gr/m ²	≥ 45 cm	≥ 4	KA-8
50% polyester / 50% katoen	420 gr/m ²	≥ 45 cm	≥ 4	KA-46

TENCATE All Season Touring™



Samenstelling	Finish	Gewicht	Waterkolom (ISO 811)	Kleurechtheid (ISO 105 B04)	Artikel
100% polyester	acrylic coating	180 gr/m ²	≥ 60 cm	≥ 6	WR-17
100% polyester	acrylic coating	190 gr/m ²	≥ 50 cm	≥ 6	WR-517
100% polyester	acrylic coating	240 gr/m ²	≥ 85 cm	≥ 6	WR-18
100% polyester	acrylic coating	240 gr/m ²	≥ 85 cm	≥ 6	WR-3019

TENCATE All Season Residential™



Samenstelling	Finish	Gewicht	Waterkolom (ISO 811)	Kleurechtheid (ISO 105 B04)	Artikel
65% polyester / 35% polyvinylalcohol	acrylic coating	220 gr/m ²	≥ 50 cm	≥ 6	WM-17
65% polyester / 35% polyvinylalcohol	acrylic coating	280 gr/m ²	≥ 100 cm	≥ 6	WM-1
80% polyester / 20% polyvinylalcohol	acrylic coating	185 gr/m ²	≥ 60 cm	≥ 6	WM-27

Protective Fabrics
Outdoor Fabrics
 Advanced Composites
 Advanced Armour

Geosynthetics
 Industrial Fabrics
 Grass

TENCATE
 materials that make a difference