



New Hampshire			
Dated 2016	Section 593	AASHTO M288 & NTPEP	
Application	Strength Class	Fabric Structure	Product
Separation and Stabilization	Class 1 (High Strength)	Slit Filament, Woven	600X
	Class 2 (Medium Strength)		600X
	Class 3 (Low Strength)		500X, 600X
Subsurface Drainage, Separation, Stabilization, Permanent Erosion Control	Class 1 (High Strength)	Nonwoven	180N
	Class 2 (Medium Strength)		160N, 180N
	Class 3 (Low Strength)		160N, 180N
Subsurface Drainage, Separation, Stabilization	Class 1 (High Strength)	Nonwoven	
	Class 2 (Medium Strength)		
	Class 3 (Low Strength)		140N
Separation and Stabilization	Class 1 (High Strength)	Monofilament, Woven	FW404
	Class 2 (Medium Strength)		FW404
	Class 3 (Low Strength)		FW402, FW404

Disclaimer: TenCate assumes no liability for the accuracy or completeness of this information or for the ultimate use by the purchaser. TenCate disclaims any and all express, implied, or statutory standards, warranties or guarantees, including without limitation any implied warranty as to merchantability or fitness for a particular purpose or arising from a course of dealing or usage of trade as to any equipment, materials, or information furnished herewith. This document should not be construed as engineering advice.

Copyright © 2015 Nicolon Corporation. All Rights Reserved

365 South Holland Drive Tel 706 693 2226 Fax 706 693 4400
 Pendergrass, GA 30567 Tel 888 795 0808 www.mirafi.com

