



## Mirafi® Dewatering Bag for Stormwater Sediment Control

TenCate™ develops and produces materials that function to increase performance, reduce costs and deliver measurable results by working with our customers to provide advanced solutions.

The Difference Mirafi® Dewatering Bags Make:

- **Compliance.** Stormwater management regulations are a key component of the Environmental Protection Agency's (EPA) Clean Water Act. This device helps maintain ground water quality, reduce pollutants, and safely deal with flooding as regulated through the National Pollution Discharge Elimination System (NPDES), Phase I & II.
- **Filtration.** Consistent fabric coverage provides steady filtration and flow characteristics as a best management practice. High permittivity properties provide high flow rate while providing excellent soil particle retention for a stormwater filtering system.

- **Cost Effective.** Mirafi® Dewatering Bags provide an economical solution for many stormwater applications.

### APPLICATIONS

Mirafi® Dewatering Bags are designed to control suspended sediment in water pumping applications. When the pumped water reaches the Mirafi® Dewatering Bag, the suspended sediment is captured by the bag.

There are several features and benefits to using Mirafi® Dewatering bags:

- Easily installs onto discharge hose.
- Easier and more convenient to use than sediment traps or other alternatives.
- Fabricated from a TenCate™ geotextile, the leader in geosynthetic applications.
- Available in three standard sizes:  
3x3ft, 6x6ft, 10x15ft, 15x15ft.

### INSTALLATION GUIDELINES

Place lifting straps (not included) under the unit to facilitate removal after use. Unfold the Mirafi® Dewatering Bag on a stabilized drainage area such as: Mirafi® G-Series drainage composites; dense vegetation; straw; or gravel. Insert discharge hose from pump into the Mirafi® Dewatering Bag a minimum of six inches (6") and tightly secure with attached strap to prevent unfiltered water from flowing out of the unit. If using optional absorbents, place absorbent boom into the Mirafi® Dewatering Bag.

**Maintenance:** Replace the dewatering bag when 1/2 full of sediment or when the pump discharge has reduced to an impractical rate. If using optional oil absorbents; remove and replace absorbent when near saturation.


*These guidelines serve as a general basis for installation. Detailed instructions are available from your TenCate™ representative.*



# Mirafi® Dewatering Bag for Stormwater Sediment Control

## Technical Data

Properties (MARV)	Test Method	Units	180N
Grab Tensile Strength	ASTM D4632	lbs (N)	205 (912)
Grab Tensile Elongation	ASTM D4632	%	50
CBR Puncture Strength	ASTM D6241	lbs (N)	500 (2224)
Trapezoid Tear Strength	ASTM D4533	lbs (N)	80 (356)
Apparent Opening Size (AOS)	ASTM D4751	(mm)	(0.18)
		U.S. Sieve	80
Permittivity	ASTM D4491	sec <sup>-1</sup>	1.4
Flow Rate	ASTM D4491	gal/min/ft <sup>2</sup>	95
		(l/min/m <sup>2</sup> )	(3870)
UV Resistance (at 500 hours)	ASTM D4355		70
		% strength retained lb (kg)	



TenCate™ Geosynthetics North America assumes no liability for the accuracy or completeness of this information or for the ultimate use by the purchaser. TenCate™ Geosynthetics North America disclaims any and all express, implied, or statutory standards, warranties or guarantees, including without limitation any implied warranty as to merchantability or fitness for a particular purpose or arising from a course of dealing or usage of trade as to any equipment, materials, or information furnished herewith. This document should not be construed as engineering advice.

Mirafi® is a registered trademark of Nicolon Corporation.

© 2010 TenCate Geosynthetics North America

PDS.DBAG.0911

365 South Holland Drive Tel 800 685 9990  
Pendergrass, GA 30567 Tel 706 693 2226

Fax 706 693 4400  
www.mirafi.com

